

707 Ex

CERTIFICATION



Ⓜ II 2 G Ex ia IIC T4



N.I. Class 1 Div. 2 Groups A-D

PRACTICAL

The fast, one-handed tool for loop checks in Ex zones. The 707Ex is a loop calibrator for use in ex-hazardous areas classified as Zone 1 and 2.

Loop Calibrator **FLUKE 707 Ex** FOR ZONE 1, 2 AND DIV 2

FEATURES & FUNCTIONS

- Large display and simple, quick click push rotary button for easy one-handed operation.
- Simultaneous mA and % readout for quick, easy, interpretation of readings.
- mA accuracy of 0.015 %
- 1 µA resolution for mA source, simulate and measure.
- Push button with 25 % steps for fast, easy linearity checks.
- 0-100 % "span check" for fast confirmation of zero and span.
- Internal loop supply, so you can power and read a transmitter at the same time.
- Measures up to 28 V dc.
- 0-20 mA or 4-20 mA default start up modes.
- HART® compatible resistance is connected in series with the loop supply for compatibility with HART® communicators.

STANDARD DELIVERY

- 707Ex
- Ex-Holster
- Safety designed test leads
- Alligator test clips
- Battery
- CD-ROM
- Calibration Certificate
- Instruction manual

FOR TESTING CURRENT LOOPS

ZONE 1 / CLASS I DIV. 2



TECHNICAL DATA

Ambient temperature	-10 °C to +50 °C
Storage temperature	-30 °C to +60 °C
Maximum voltage	28 Volt
Relative humidity	95 % (0 °C to +30 °C); 75 % (+30 °C to +40 °C); 45 % (-40 °C to +50 °C)
Power supply	1x 6LR61, type approved
Operating time	18 hours typical, at 12 mA
Dimensions (HxWxD)	164 x 75 x 47 mm (with holster)
Weight	350 g (with holster)

SUMMARY SPECIFICATIONS (18 °C TO 28 °C. ONE YEAR)

Function	Range	Resolution	Accuracy
Voltage measure	0 to 28 V	0.001 V	±(0.015 % v. MW. +2 Digits)
mA measure	0 to 24 mA	0.001 mA	±(0.015 % v. MW. +2 Digits)
mA source ¹	0 to 24 mA	0.001 mA	±(0.015 % v. MW. +2 Digits)
mA simulate ²	0 to 24 mA	0.001 mA	±(0.015 % v. MW. +2 Digits)
Loop supply	24 V	n. z.	24 V ± 1 V DC

Temperature Coefficient, -10 to 18 °C, 28 to 55 °C: ± 0.005 % of range per °C;

¹ Max load, 700 Ohms at 20 mA

² Max applied voltage for simulation, 28 V

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com

¹ also responsible for Austria

Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com

² also responsible for Belgium and Luxembourg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com

³ also responsible for Algeria, Egypt, Morocco, Libya and Tunisia

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

ecom instruments GmbH
Merkurstraße 2
6210 Sursee
Phone +41 4 19 21 60 00
Fax +41 4 19 22 00 08
info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com

Americas

USA

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
info.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sg@ecom-ex.com



Find your local ecom partner at www.ecom-ex.com