



**ZONE 1/21  
CL I / DIV 1**

## < IS330.1 >

**Rugged, safe and built for any challenge!**

**Highlights:**  
Android™ 9, Bluetooth® 5,  
huge internal memory 64 GB,  
multifunctional ISM interface,  
amplified loudspeaker, SOS-  
key, PTT-key, MCPTT ready

➤ Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ➤ © 2019 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1027MD01REV01\_EN\_05.2020

## TECHNICAL FEATURES



ATEX approval applied for:  
EX-Zone 1/21  
⊗ II 2G Ex ib IIC T4 Gb  
⊗ II 2D Ex ib IIIC T135°C  
Db IP6X



IECEx approval applied for:  
EX-Zone 1/21  
Ex ib IIC T4 Gb  
Ex ib IIIC T135°C Db IP6X



Approval in North America applied for:  
Class I, II, III Division 1  
Groups A B C D E F G, T4  
Intrinsically Safe



Android™ 9



2,4GHz + 5GHz: IEEE  
802.11a/b/g/n/ac/e/k/r/h  
with max. 8 connections  
hotspot



GSM 850/900/1800/  
1900 MHz  
WCDMA: UMTS B1/2/4/5/8  
LTE-TDD: B38/B39/B40/B41  
LTE-FDD: B1/2/3/4/5/7/8/12  
with MFBI B13/14/17/20/25/  
26/28A/28B/29/30/66  
TD-SCDMA: B34/B39



Bluetooth® 5



Size: 152,8 x 62 x 26,7,  
weight: 306,5 g



External memory  
microSD up to 128 GB



2 cameras: 13 MP AF  
rear camera and 5 MP FF  
front camera



Qualcomm Snapdragon  
SDM660 Octa-Core  
(Kryo Gold-Quad cores  
2.2GHz; Kryo Silver-Quad  
cores 1.8GHz),  
4 GB RAM,  
64 GB internal memory



Dual nano SIM



Near Field  
Communication



SOS-key  
Loneworkeer protection  
LWP ready (third party  
application required,  
based on country specific  
regulations)



Universal, lateral  
ISM interface

## FURTHER FEATURES



Waterproof: 1 hour  
up to 2 m, impervious to  
dust and microparticles



Operation range from  
-20 °C to 60 °C



Drop-protection,  
tested against: vibrations,  
shock and extreme  
temperatures.



2,6" Gorilla Glass®  
3. generation,  
resolution 320 x 432 pixel



Usable with gloves



Amplified loudspeaker



4050 (typ. 4200) mAh  
replaceable battery,  
3,8V; 14,98Wh



GPS, A-GPS, Glonass,  
Beidou, Galileo



G-sensor, gyroscope,  
gravity, ambient light,  
magnetic- and proximity



Push-To-Talk  
PTT ready (third party  
application required,  
based on country specific  
regulations)

## CONTENTS

Mobile phone, battery, i.safe PROTECTOR 2.0 USB cable, charger, quick start manual and safety instructions