

## ZONE 2/22



### IS730.2

The IS730.2 is the new ATEX-smartphone for use in zone 2/22. It combines high performance technology (Android™ 6.0, LTE, wireless charging) with highest robustness and modern design.

#### TECHNICAL FEATURES

<p>ATEX approval: EX-zone 2/22 © II 3G Ex ic IIC T4 Gc IP54 © II 3D Ex ic IIIB T135°C Dc IP54</p>	<p>IECEx approval: EX-zone 2/22 Ex ic IIC T4 Gc IP54 Ex ic IIIB T135°C Dc IP54</p>	<p>Android 6.0</p>	<p>2G: GSM 850/900/1800/ 1900 MHz 3G: WCDMA 850/900/ 1900/2100 MHz 4G: LTE-FDD Band 1/3/7/20/28, LTE-TDD Band 39/40/41</p>	<p>WiFi IEEE 802.11 b/g/n</p>
<p>Bluetooth® 4.0</p>	<p>MT6735 (Quad Core 1.3 GHz), 2 GB RAM, 16 GB internal memory, 10 GB assessable</p>	<p>size: 156 x 82 x 14 mm, weight: 245 g</p>	<p>external memory microSD up to 32 GB</p>	<p>Dual micro SIM</p>
<p>2 cameras: 13 MP rear camera and 5 MP front camera</p>	<p>Near Field Communication</p>	<p>wireless charging: Qi standard</p>	<p>USB OTG</p>	

#### FURTHER FEATURES

<p>waterproof: 30 min. up to 2 m, impervious to dust and micropar- ticles</p>	<p>operation range from -20 °C to 60 °C</p>	<p>drop-protection, tested against: extreme temperatures, barome- tric pressure, humidity and vibrations.</p>	<p>5" (12.70 cm) HD Bright View Gorilla Glass 3, capacitive touchscreen with a resolution of 1280 x 720 pixel</p>	<p>for use with gloves</p>
<p>amplified loudspeaker</p>	<p>3.020 mAh battery, standby 450 hrs., talktime 2G/3G: 480 min./420 min.</p>	<p>GPS, AGPS, GLONASS, BeiDou (localization and navigation via application of another provider)</p>	<p>G-sensor, gyroscope light sensor, magnetic sensor, pressure sensor, proximity sensor</p>	<p>push-to-talk (application of another provider needed)</p>

#### CONTENTS

Mobile phone with integrated battery, charger, USB cable, quick start manual and safety instructions