

The IS310.2 is the powerful mobile phone with **Android** operating system. The key-operated phone provides many technical advantages: NFC, Dual SIM, LED torch and SOS-key.

- Approval (a) II 3G Ex ic IIC T4 Gc IP54
-) Operating system Android 4.4
- Measurements weight: 230 g, size: 140 x 63 x 26 mm
- Display 2.4" RugDisplay Glass with a resolution of 240 x 320 px
- Camera
- 5 MP rear, 0,3 MP front

> Wireless communication

- Bluetooth® 4.0, GPS, AGPS, Wi-Fi®, NFC SOS-key, PTT-key, LWP ready*, PTT ready*
-) Processor MT6572M, 1.3 GHz

) Memory 512 MB RAM 4 GB internal memory 1.21 GB accessible

external memory microSD up to 32 GB

> Frequencies 3G: GSM 850/900/1800/1900 MHz WCDMA 900/1800/2100 MHz

) Battery 3600 mAh: standby up to 300 hrs., talktime up to 300 min.

) Dual micro SIM

Safety functions powerful LED torch,

Degree of protection

The IS520.2 is an industrial smartphone with current technology. It combines modern design, updated technology and robustness of an industrial product.

Approval

Ex ic IIC T4 Gc IP64 Ex ic IIIC T135°C Db IP64

Operating system Android 7.1

resolution of 854 x 480 px

Camera

8 MP rear, 5 MP front

> Wireless communication Bluetooth® 4.1 LE, Wi-Fi®, GPS, AGPS, GLONASS, BeiDou, NFC

Measurements weight: 325 g, size: 155 x 80 x 25 mm

Display 4.5" HD RugDisplay Glass multi capacitive touchscreen with a

) Processor

Qualcomm Snapdragon 625 (MSM8953), 2 GHz

) Memory 3 GB RAM, 32 GB internal

memory, 22 GB accessible, external memory microSD up to 32 GB

> Frequencies Display GSM: 850/900/1800/1900MHz WCDMA: 900/1800/2100 or 850/1900/2100MHz

4G/LTE) Battery 3600 mAh

) Quick charge

Safety functions SOS-kev, PTT-kev LWP ready*, PTT ready*

Degree of protection

The IS740.2 is the ATEX smartphone from i.safe MOBILE with Android 7.1 operating system, current technology and a powerful battery.

) Approval (a) II 3G Ex ic IIC T4 Gc IP54

Operating system Android 7.1

Measurements weight: 226 g, size: 153 x 77 x 15 mm

4.7" HD Bright View Gorilla Glass 3, capacitive touchscreen with a resolution of 1280 x 720 px

Camera 13 MP rear, 5 MP front

Wireless communication Bluetooth® 4.1 LE, Wi-Fi®, GPS AGPS, GLONASS, BeiDou, NFC

Memory 3 GB RAM, 32 GB internal memory, 24 GB accessible, external memory microSD up to 32 GB

) Processor Qualcomm Snapdragon 430

(MSM8937) > Frequencies

2G: GSM 850/900/1800/1900 MHz 3G: WCDMA 850/900/1900/2100 4G: LTE FDD: B1/B3/B5/B7/B8/ B20/B28 LTE TDD: B38/ B39/B40/B41 TD SCDMA: B34/B39

Battery 3950 mAh; standby up to 200 hrs., talktime 480 min.

Dual nano SIM

Safety functions LWP ready*, PTT ready* Degree of protection

(MSM8953), 2 GHz

The IS910.2 is a 8" tablet for use in ATEX zones 2/22. It is highly robust, powerful and offers many technical advantages: **6.000 mAh** battery, Qualcomm Snapdragon processor, NFC, Android 8.0 etc.

Approval Ex x ic IIC T4 Gc IP64 Ex ic IIIC T135°C Dc IP64

) Operating system Android 8.0

Measurements weight: 850 g, size: 235 x 154 x 23 mm

Display 8" RugDisplay Glass multi capacitive touchscreen with a resolution of 1200 x 1920 px

Camera 8 MP rear, 5 MP front

> Wireless communication Bluetooth® 4.1 LE, Wi-Fi®, GPS, AGPS, GLONASS, BeiDou, NFC

Processor Qualcomm Snapdragon 625) Memory

3 GB RAM, 32 GB internal memory, 24 GB accessible, external memory microSD up to 32 GB

> Frequencies 2G: GSM 850/900/1800/1900MHz 3G: WCDMA 900/1800/2100 or 850/1900/2100 MHz 4G: LTE FDD EU: B1/B3/B7/B20/B28 LTE FDD US: B2/B4/B7/B17 LTE TDD: B38/B39/B40/41

TD: B34/B39) Battery 6000 mAh

) Quick charge

Safety functions SOS-kev, LWP ready*, PTT ready*

> Degree of protection

I.SAFE MOBILE - MOBILE PHONES AND **SMARTPHONES FOR ATEX ZONE 1 AND 2**

The i.safe MOBILE GmbH is your **partner** for the development, approval and marketing of **explosion-proof mobile communication devices**. With more than 15 years of experience, i.safe MOBILE GmbH belongs to most innovative and well-established experts worldwide.

Our priority is development of practice-oriented products based on the legal requirements. We place **great emphasis on quality** not only in the development of our products, but also by offering customized service to your needs and detailed maintenance plan. To improve upon costomer relationship we rely on our authorized worldwide partner network. In case you need an optimal solution from a technical and economic point of view - i.safe MOBILE GmbH is your expert.

We look forward to have a long-term and trusting relationship with you.

All i.safe MOBILE products are standard equipped with the following specifications:



operation range

cleaning with

from -20 °C to 60 °C

germicide possible



RugDisplay-Glass





amplified speaker

impervious to dust

and microparticles

i.safe MOBILE GmbH

i_Park Tauberfranken 10, 97922 Lauda-Koenigshofen, Germany info@isafe-mobile.com

WWW.ISAFE-MOBILE.COM

i.safe MOBILE YOUR GLOBAL EXPERT FOR MOBILE

COMMUNICATIONS AND SOLUTIONS

WWW.ISAFE-MOBILE.COM

*Push-to-talk / LWP (third party application provided)



The IS320.1 is the powerful mobile phone with **Android™ operating system.** The key-operated phone provides many technical advantages: NFC, LED torch and SOS-key.

- Approval Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X
- Operating system Android 4.4
- Measurements weight: 230 g,
- size: 140 x 63 x 26 mm) Display
- 2.4" RugDisplay Glass with a resolution of 240 x 320 px
- Camera 2 MP rear
- Wireless communication Bluetooth® 4.0, GPS, AGPS, Wi-Fi®, NFC

*Push-to-talk / LWP (third party application provided)

) Processor

- MT6572M, 1.3 GHz) Memory
- 512 MB RAM, 4 GB internal memory, 1.21 GB accessible, external memory microSD up to 32 GB
- > Frequencies GSM 850/900/1800/1900 MHz.
-) Battery
- 1900 mAh Safety functions
 - powerful LED torch, SOS-key, PTT-key LWP ready*, PTT ready*
 -) Degree of protection

The IS520.1 is an industrial smartphone with current technology. It combines modern design, **updated technology and robustness** of an industrial product.

- Approval II 2G Ex ib IIC T4 Gb Ex ib IIC T4 Gb
- Operating system Android 7.1
- Measurements weight: 325 g,
- WCDMA 900/1800/2100 MHz Display
 - Camera
 - - > Wireless communication

- Ex ib IIIC T135°C Db IP6X
- size: 155 x 80 x 25 mm
- 4.5" HD RugDisplay Glass multi capacitive touchscreen with a resolution of 854 x 480 px
- 8 MP rear, 5 MP front
- Bluetooth® 4.1 LE, Wi-Fi®, GPS, AGPS, GLONASS, BeiDou, NFC

-) Processor Qualcomm Snapdragon 625 (MSM8953), 2 GHz
- Memory 3 GB RAM, 32 GB internal memory, 22 GB accessible, external memory microSD up to 32 GB
- > Frequencies GSM: 850/900/1800/1900MHz WCDMA: 900/1800/2100 or 850/1900/2100MHz 4G/LTE
-) Batterv 3600 mAh
-) Quick charge
 - Safety functions SOS-key, PTT-key LWP ready*, PTT ready*
 - Degree of protection

The IS910.1 is a highly robust and powerful 8" tablet and offers many technical advantages: 8.400 mAh battery, 2 GHz Qualcomm Snapdragon processor, NFC, Android 8.0 etc.

) Memory

up to 32 GB

Frequencies

TD: B34/B39

8400 mAh

) Quick charge

Battery

850/1900/2100 MHz

LTE FDD US: B2/B4/B7/B17

LTE TDD: B38/B39/B40/41

3 GB RAM, 32 GB internal

memory, 24 GB accessible,

external memory microSD

2G: GSM 850/900/1800/1900MHz

4G: LTE FDD EU: B1/B3/B7/B20/B28

3G: WCDMA 900/1800/2100 or

- Approval (a) II 2G Ex ib IIC T4 Gb Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X
- Operating system Android 8.0
- Measurements weight: 880 g, size: 235 x 154 x 23 mm
- Display 8" RugDisplay Glass multi capacitive touchscreen with a resolution of 1200 x 1920 px
- Camera 8 MP rear, 5 MP front

Qualcomm Snapdragon 625

(MSM8953), 2 GHz

) Processor

- Wireless communication Bluetooth® 4.1 LE, Wi-Fi®, GPS, AGPS, GLONASS, BeiDou, NFC
- > Safety functions SOS-key, LWP ready*, PTT ready*
- > Degree of protection

The HMT-1Z1 is the world's first intrinsically safe hands-free Android tablet class wearable computer for industrial workers. Use it in wet, dusty, hot, dangerous and loud hydrocarbon environments.

2.0 GHz Qualcomm Snapdragon

625 with Adreno 506 GPU -

2 GB RAM, 16 GB internal

Includes applications

Degree of protection

memory, external memory

document navigator, camera

with barcode-reader, video

Memory

microSD

3400 mAh

OpenGL ES3.1 & OpenCL 2.0

-) Approval) Processor (a) II 2G Ex ib IIC T4 Gb Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X
- Operating system Android[™] 6.0.1 + WearHF[™] hands-free interface
- Measurements weight: 430 g
- Display 20° field-of-view, 1 m fixed focus, 24-bit color LCD, 0.33" diagonal, out-door visible, resolution WVGA 854 x 480 px
-) Camera 16 MP 4-image stabilized, PDAF with LED flashlight
- Wireless communication Bluetooth® 4.1 LE, Wi-Fi®, GPS, GLONASS, BeiDou, Baidu A-GPS

The wireless remote speaker mic RG-RSM1 connects via use of **push-to-talk** applications.

- (a) II 2G Ex ib IIC T4 Gb Ex ib IIC T4 Gb
- Measurements weight: 126 g,
- recorder, media player

Bluetooth to the mobile phone and enables a professional

- Approval
- Ex ic IIIB T135°C Dc IP54 Miscellaneous control
- size: 87 x 56 x 25 mm) Battery 950 mAh
-) Operation range from -20° to +60°C

> Safety functions

-) Speaker amplified with >100 dB
-) Battery capacity Charging Micro USB) Memory
- for 1000 readings PTT-key, intercom and volume Wireless communication Bluetooth®
 - Reading distance 1 ... 3 cm
 -) OLED-display

Features of IS-MP.1:

- Approval II 2G Ex ib IIC T4 Gb Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X
-) Measurements weight: 130 g, size: 190 x 30 x 35 mm
- Degree of protection

The IS-MP.1 and the IS-MP.2 are handheld readers for easy and efficient **reading of RFID/NFC-TAGs.** The TAG information can be viewed directly on the OLED display, transferred via Bluetooth or read from the storage via USB.

- > RFID/NFC tag-reader for 2000 Bluetooth readings LF 125 kHz, LF 134.2 kHz,
 - FDX-B + HDX, HF and NFC 13.56 MHz, UHF 868 MHz
 - Allows individual configuration. > App for Remote Control
 - available > Real-time clock
 - Vibration feedback

Features of IS-MP.2:

- Approval (a) II 3G Ex ic IIC T4 Gc IP54 Ex ic IIC T4 Gc IP54 Ex ic IIIB T135°C Dc IP54
- Measurements weight: 125 g, size: 190 x 30 x 35 mm
- Degree of protection

) is a fe MOBILE and the isafe MOBILE logo are registered trademarks of isafe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License, Bluetooth* is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners.) © 2018 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1000MF02REV02_EN_10.2018